



# Documentation Sheet

 <b>National Aerospace Laboratories</b>		<b>Class:</b> Unrestricted <b>No. of Copies:</b> 6
<b>Title:</b> <i>Active Cancellation in Adaptive Array with Non-uniform Inter-element Spacing</i>		
<b>Author/s:</b> Hema Singh, Priyesh, R M Jha		
<b>Division:</b> ALD		<b>NAL Project No:</b> A-1-178
<b>Document No:</b> PD AL 1208		<b>Date of issue:</b> February 2012
<b>Contents:</b> <input type="text" value="33"/> Pages <input type="text" value="30"/> Figures <input type="text" value="2"/> Tables <input type="text" value="7"/> References		
<b>External Participation:</b> Nil		
<b>Sponsor:</b> x		
<b>Approval:</b> Chairman, Systems Engineering Cluster		
<b>Remarks:</b> x		
<b>Keywords:</b> Active cancellation, Non-uniform spacing, Modified Improved LMS algorithm, Adapted pattern.		
<b>Abstract:</b> <p>The radiation pattern of phased array depends on the geometrical configuration, in particular on the inter-element spacing. In this document the suppression capabilities of linear/planar array is studied when the antenna elements are placed at non-uniform/random spacing. The modified improved LMS algorithm is employed to generate the optimum weights, and hence the adapted pattern for such arrays. The signal scenarios consisting of single/multiple, narrowband/wideband sources, uncorrelated/correlated/coherent sources are considered.</p>		